

# VENTO THREE

VENTO SERIES



## SPECIFICATIONS

- Three-way line array system.
- Includes one 12" neodymium low weight loudspeaker of high magnetic strength and optimal thermal dissipation.
- Includes one 10" neodymium low weight loudspeaker of high magnetic strength and optimal thermal dissipation.
- Includes one 1.4" neodymium compression driver coupled with a W&dB wave guide.
- Duralumin and galvanized steel rigging hardware integrated into each cabinet.
- 7° vertical and 120° horizontal waveguide dispersion beam.
- Low frequency ranges at high SPL.
- The bass reflex system works from 60 Hz to 20 KHz.

*This cabinet is made of birch Wissa-Plywood. The rigging support system is manufactured in aeronautical spec steel and aluminum. Speakon NL8 connectors are used for power amplifier connections. The paint finish is high resistance polyurea.*

TECHNICAL DATA	VENTO THREE
Transducers	1x 12"/1x 10"/1x 1,4"
Coverage	120° Horiz. x 7° Vertical
Nominal impedance	LF 8Ω - MF 8Ω - HF 8Ω
Power AES	1180 W
Maximun Peak SPL	139 dB SPL
Frequency Range	50 Hz to 20 kHz
Sensibility(1W@1m)	1w @ 1m: 99 dB
Weigth	43 Kg
Enclosure Geometry	Trapezoidal
Angle adjustment	1° to 1°
Dimensions(WxHxD)	867 x 330 x 473 mm
Enclosure Material	Birch Plywood 15 mm
Rigging	Steel & Aluminium
Finish	Polyurea
Colour	Black
Connections	2 x Speakon NL8

