

VENTO ONE

VENTO SERIES



SPECIFICATIONS

- Two-way active line array system.
- Includes one 12" neodymium low weight loudspeaker of high magnetic strength and big thermal dissipation.
- Includes one 1.4" compression driver coupled to a W&dB wave guide.
- Duralumin and galvanized steel integrated rigging hardware into each cabinet.
- The waveguides dispersion beam is 7° vertical and 120° horizontal.

This cabinet is made of birch Wissa-Plywood. The rigging support system is manufactured in aeronautical spec aluminum and steel. Speakon NL4 connectors are used for power amplifier connections .

The paint finish is high resistance polyurea.

TECHNICAL DATA	VENTO ONE
Transducers	1X 12"/1X 1,4"
Coverage	120° H x 7° V
Nominal impedance	LF 8Ω - HF 8Ω
Power AES	800W
Maximun Peak SPL	138 dB SPL
Frequency Range	50 Hz to 18 kHz
Sensibility(1W@ 1m)	1w@ 1m: 98 dB
Weigth	28 Kg
Enclosure Geometry	Trapezoidal
Angle adjustment	1° to 1°
Dimensions(WxHxD)	669 x 328 x 489 mm
Enclosure Material	Birch Plywood 15/18 mm
Rigging	Steel & Aluminum
Finish	Polyurea
Colour	Black
Connections	2 x Speakon NL4

